



51102 Series



This is a 120VAC single phase 19" rack mount power distribution unit that is 1 "U" (1 ¾") high and 9" deep. The 51102 series PDU's have eight NEMA 5-20R receptacles on the rear panel. This series comes standard with a branch rated circuit breaker. Standard options like remote control, filtering, and other options are available. The 51102 series comes in various current ratings depending on model, see the specs below.

Model Selection Guide

| Model Number | 51102-00005-015 | 51102-00005-020 | 51102-00005-030 |
|---------------------------------|------------------|------------------|------------------|
| Height x Width x Depth: | 1.75" x 19" x 9" | 1.75" x 19" x 9" | 1.75" x 19" x 9" |
| Voltage Input/Output (50-60Hz): | 120VAC | 120VAC | 120VAC |
| Current Input: | 15Amps | 20Amps | 30Amps |
| Current Output De-rated: | 12Amps | 16Amps | 24Amps |
| Full Load Volt/Amp De-rated: | 1440VA | 1920VA | 2880VA |
| NEMA Outlets: | 8, 5-20R | 8, 5-20R | 8, 5-20R |
| Circuit Breaker w/Kick Guard: | 15/15 | 20/20 | 15/15 |
| Power Cord/Length (rear panel): | 14/3 15ft | 12/3 15ft | 10/3 15ft |
| NEMA Power Input Plug: | 5-15P | L5-20P | L5-30P |
| Front Panel Color | Clear Zinc | Clear Zinc | Clear Zinc |

Standard Options Available:

| | | | |
|--|-----|-----|-----|
| Customer Private Label: | Yes | Yes | Yes |
| EMI Filter w/ transient protection: | Yes | Yes | Yes |
| Remote Control : | Yes | Yes | Yes |
| Painted Front Panel: | | | |
| Interact Power color Dark Gray #26008 | Yes | Yes | Yes |
| or Customer Specified Color | Yes | Yes | Yes |
| Redundant Input available | Yes | Yes | Yes |

Power Distribution Units Engineered to Reduce Risk and Improve Performance.

Interact Power, Inc. * 1325 N Red Gum Ave, Suite 7 * Anaheim, CA 92806 * T: 714.632.5005 * F: 714.632.5006



51103 Series



This is a 120VAC or 230VAC single phase 19" rack mount power distribution unit that is 1 "U" (1 3/4") high and 9" deep. The 51103 series PDU's have eight NEMA C13 receptacles on the rear panel. The input is an IEC320 C20, and is located on the rear with an attached strain relief. It has no power cord. A country specific power cord may be ordered separately. This series comes standard with a branch rated circuit breaker. Standard options like remote control, filtering, and other options are available. The 51103 series comes in various current ratings depending on model, see the specs below.

Model Selection Guide

| Model Number | 51103-00005-015 | 51103-00005-020 | 51103-00005-030 |
|--------------------------------------|------------------|------------------|------------------|
| Height x Width x Depth: | 1.75" x 19" x 9" | 1.75" x 19" x 9" | 1.75" x 19" x 9" |
| Voltage Input/Output (50-60Hz): | 120VAC or 230VAC | 120VAC or 230VAC | 120VAC or 230VAC |
| Current Input: | 15Amps | 20Amps | 30Amps |
| Current Output De-rated: | 12Amps | 16Amps | 24Amps |
| Maximum Full Load Volt/Amp De-rated: | 2760VA | 3680VA | 5520VA |
| IEC 320 Outlets: | 8, C13 | 8, C13 | 8, C13 |
| Circuit Breaker w/Kick Guard: | 15/15 | 20/20 | 15/15 |
| Power Cord/Length (rear panel): | n/a | n/a | 32A "HAR"/15ft |
| IEC 320 Power Input Connector: | C20 | C20 | None |
| Front Panel Color | Clear Zinc | Clear Zinc | Clear Zinc |

Standard Options Available:

| | | | |
|--|-----|-----|-----|
| Customer Private Label: | Yes | Yes | Yes |
| EMI Filter w/ transient protection: | Yes | Yes | Yes |
| Remote Control : | Yes | Yes | Yes |
| Painted Front Panel: | | | |
| Interact Power color Dark Gray #26008 | Yes | Yes | Yes |
| or Customer Specified Color | Yes | Yes | Yes |
| Redundant Input available | Yes | Yes | Yes |

Power Distribution Units Engineered to Reduce Risk and Improve Performance.

Interact Power, Inc. * 1325 N Red Gum Ave, Suite 7 * Anaheim, CA 92806 * T: 714.632.5005 * F: 714.632.5006



51108 Series



This is a 280VAC or 240VAC 3-wire (L-L-G) 19" rack mount power distribution unit that is 1 "U" (1 ¾") high and 9" deep. The 51108 series PDU's have eight NEMA 6-20R receptacles on the rear panel. This series comes standard with a branch rated circuit breaker. Standard options like remote control, filtering, and other options are available. The 51108 series comes in various current ratings depending on model, see the specs below.

Model Selection Guide

| Model Number | 51108-00005-015 | 51108-00005-020 | 51108-00005-030 |
|--------------------------------------|------------------|------------------|------------------|
| Height x Width x Depth: | 1.75" x 19" x 9" | 1.75" x 19" x 9" | 1.75" x 19" x 9" |
| Voltage Input/Output (50-60Hz): | 208VAC or 240VAC | 208VAC or 240VAC | 208VAC or 240VAC |
| Current Input: | 15Amps | 20Amps | 30Amps |
| Current Output De-rated: | 12Amps | 16Amps | 24Amps |
| Maximum Full Load Volt/Amp De-rated: | 2880VA | 3840VA | 5760VA |
| NEMA Outlets: | 8, 6-20R | 8, 6-20R | 8, 6-20R |
| Circuit Breaker w/Kick Guard: | 15/15 | 20/20 | 25/25 |
| Power Cord/Length (rear panel): | 14/3 15ft | 12/3 15ft | 10/3 15ft |
| NEMA Power Input Plug: | 6-15P | L6-20P | L6-30P |
| Front Panel Color | Clear Zinc | Clear Zinc | Clear Zinc |

Standard Options Available:

| | | | |
|--|-----|-----|-----|
| Customer Private Label: | Yes | Yes | Yes |
| EMI Filter w/ transient protection: | Yes | Yes | Yes |
| Remote Control : | Yes | Yes | Yes |
| Painted Front Panel: | | | |
| Interact Power color Dark Gray #26008 | Yes | Yes | Yes |
| or Customer Specified Color | Yes | Yes | Yes |
| Redundant Input available | No | No | No |

Power Distribution Units Engineered to Reduce Risk and Improve Performance.

Interact Power, Inc. * 1325 N Red Gum Ave, Suite 7 * Anaheim, CA 92806 * T: 714.632.5005 * F: 714.632.5006



51112 Series



This is a 120VAC single phase 19" rack mount power distribution unit that is 1 "U" (1 3/4") high and 9" deep. The 51112 series PDU's have eight NEMA 5-20R receptacles on the rear panel that can be individually operated with one of eight rocker switches on the front panel. This series comes standard with a branch rated circuit breaker. Standard options like remote control, filtering, and other options are available. The 51112 series comes in various current ratings depending on model, see the specs below.

Model Selection Guide

| Model Number | 51112-00005-015 | 51112-00005-020 | 51112-00005-030 |
|--|------------------|------------------|------------------|
| Height x Width x Depth: | 1.75" x 19" x 9" | 1.75" x 19" x 9" | 1.75" x 19" x 9" |
| Voltage Input/Output (50-60Hz): | 120VAC | 120VAC | 120VAC |
| Current Input: | 15Amps | 20Amps | 30Amps |
| Current Output De-rated: | 12Amps | 16Amps | 24Amps |
| Full Load Volt/Amp De-rated: | 1440VA | 1920VA | 2880VA |
| NEMA Outlets: | 8, 5-20R | 8, 5-20R | 8, 5-20R |
| Circuit Breaker w/Kick Guard: | 15/15 | 20/20 | 15/15 |
| Rocker Switches for Individual receptacle control: | Yes | Yes | Yes |
| Power Cord/Length (rear panel): | 14/3 15ft | 12/3 15ft | 10/3 15ft |
| NEMA Power Input Plug: | 5-15P | L5-20P | L5-30P |
| Front Panel Color | Clear Zinc | Clear Zinc | Clear Zinc |

Standard Options Available:

| | | | |
|--|-----|-----|-----|
| Customer Private Label: | Yes | Yes | Yes |
| EMI Filter w/ transient protection: | Yes | Yes | Yes |
| Remote Control : | Yes | Yes | Yes |
| Painted Front Panel: | | | |
| Interact Power color Dark Gray #26008 | Yes | Yes | Yes |
| or Customer Specified Color | Yes | Yes | Yes |
| Redundant Input available | Yes | Yes | Yes |

Power Distribution Units Engineered to Reduce Risk and Improve Performance.

Interact Power, Inc. * 1325 N Red Gum Ave, Suite 7 * Anaheim, CA 92806 * T: 714.632.5005 * F: 714.632.5006



51113 Series



This is a 120VAC or 230VAC single phase 19" rack mount power distribution unit that is 1 "U" (1 3/4") high and 9" deep. The 51113 series PDU's have eight IEC320 C13 receptacles on the rear panel that can be individually operated with one of eight rocker switches on the front panel. This series comes standard with a branch rated circuit breaker. Standard options like remote control, filtering, and other options are available. The 51113 series comes in various current ratings depending on model, see the specs below.

Model Selection Guide

| Model Number | 51103-00005-015 | 51103-00005-020 | 51103-00005-030 |
|--|------------------|------------------|------------------|
| Height x Width x Depth: | 1.75" x 19" x 9" | 1.75" x 19" x 9" | 1.75" x 19" x 9" |
| Voltage Input/Output (50-60Hz): | 120VAC or 230VAC | 120VAC or 230VAC | 120VAC or 230VAC |
| Current Input: | 15Amps | 20Amps | 30Amps |
| Current Output De-rated: | 12Amps | 16Amps | 24Amps |
| Maximum Full Load Volt/Amp De-rated: | 2760VA | 3680VA | 5520VA |
| IEC 320 Outlets: | 8, C13 | 8, C13 | 8, C13 |
| Circuit Breaker w/Kick Guard: | 15/15 | 20/20 | 15/15 |
| Rocker Switches for Individual receptacle control: | Yes | Yes | Yes |
| Power Cord/Length (rear panel): | n/a | n/a | 32A "HAR"/15ft |
| IEC 320 Power Input Connector: | C20 | C20 | None |
| Front Panel Color | Clear Zinc | Clear Zinc | Clear Zinc |

Standard Options Available:

| | | | |
|--|-----|-----|-----|
| Customer Private Label: | Yes | Yes | Yes |
| EMI Filter w/ transient protection: | Yes | Yes | Yes |
| Remote Control : | Yes | Yes | Yes |
| Painted Front Panel: | | | |
| Interact Power color Dark Gray #26008 | Yes | Yes | Yes |
| or Customer Specified Color | Yes | Yes | Yes |
| Redundant Input available | Yes | Yes | Yes |

Power Distribution Units Engineered to Reduce Risk and Improve Performance.

Interact Power, Inc. * 1325 N Red Gum Ave, Suite 7 * Anaheim, CA 92806 * T: 714.632.5005 * F: 714.632.5006



51122 Series



This is a 120/240VAC 4-wire (L-L-N-G) 19" rack mount power distribution unit that is 1 "U" (1 3/4") high and 9" deep. The 51122 series PDU's have eight NEMA 5-20R receptacles on the rear panel. This series comes standard with a branch rated circuit breaker. Standard options like remote control, filtering, and other options are available. The 51102 series comes in various current ratings depending on model, see the specs below.

Model Selection Guide

| Model Number | 51122-00005-015 | 51122-00005-020 | 51122-00005-030 |
|---------------------------------|------------------|------------------|------------------|
| Height x Width x Depth: | 1.75" x 19" x 9" | 1.75" x 19" x 9" | 1.75" x 19" x 9" |
| Voltage Input/Output (50-60Hz): | 120/240V~ | 120/240V~ | 120/240V~ |
| Current Input: | 15Amps | 20Amps | 30Amps |
| Current Output De-rated: | 12Amps | 16Amps | 24Amps |
| Full Load Volt/Amp De-rated: | 1440VA | 1920VA | 2880VA |
| NEMA Outlets: | 8, 5-20R | 8, 5-20R | 8, 5-20R |
| Circuit Breaker w/Kick Guard: | 15/15 | 20/20 | 2, 15/15 |
| Power Cord/Length (rear panel): | 14/4 / 15ft | 12/4 / 15ft | 10/4 / 15ft |
| NEMA Power Input Plug: | L14-20P | L14-20P | L14-30P |
| Front Panel Color | Clear Zinc | Clear Zinc | Clear Zinc |

Standard Options Available:

| | | | |
|--|-----|-----|-----|
| Customer Private Label: | Yes | Yes | Yes |
| EMI Filter w/ transient protection: | Yes | Yes | Yes |
| Remote Control : | Yes | Yes | Yes |
| Painted Front Panel: | | | |
| Interact Power color Dark Gray #26008 | Yes | Yes | Yes |
| or Customer Specified Color | Yes | Yes | Yes |
| Redundant Input available | No | No | No |

Power Distribution Units Engineered to Reduce Risk and Improve Performance.

Interact Power, Inc. * 1325 N Red Gum Ave, Suite 7 * Anaheim, CA 92806 * T: 714.632.5005 * F: 714.632.5006



51132 Series



The 51132 series is a three phase 19" rack mount power distribution unit that is 1 "u" (1 ¾") high and 9" deep. This series has eight NEMA 5-20R receptacles on the rear. This series comes standard with a branch rated circuit breaker. Standard options like remote control, filtering, and other options are available. The 51102 series comes in various current ratings depending on model, see the specs below.

Model Selection Guide

| Model Number | 51132-00005-015 | 51132-00005-020 | 51132-00005-030 |
|---|------------------|------------------|------------------|
| Height x Width x Depth: | 1.75" x 19" x 9" | 1.75" x 19" x 9" | 1.75" x 19" x 9" |
| Voltage Input/Output (50-60Hz): | 120/208V~ | 120/208V~ | 120/208V~ |
| Current Input per phase: | 15Amps | 20Amps | 30Amps |
| Current Output De-rated per phase: | 12Amps | 16Amps | 24Amps |
| Full Load Volt/Amp De-rated per phase: | 1440VA | 1920VA | 2880VA |
| Combined Full Load Volt/Amp De-rated all phase: | 4320VA | 5760VA | 8640VA |
| NEMA Outlets: | 8, 5-20R | 8, 5-20R | 8, 5-20R |
| Circuit Breaker w/Kick Guard: | 3, 15Amp | 3, 20Amp | 3, 15/15 |
| Power Cord/Length (rear panel): | 14/5 / 15ft | 12/5 / 15ft | 10/5 / 15ft |
| NEMA Power Input Plug: | L20-21P | L21-20P | L21-30P |
| Front Panel Color | Clear Zinc | Clear Zinc | Clear Zinc |

Standard Options Available:

| | | | |
|--|-----|-----|-----|
| Customer Private Label: | Yes | Yes | Yes |
| EMI Filter w/ transient protection: | Yes | Yes | Yes |
| Remote Control : | Yes | Yes | Yes |
| Painted Front Panel: | | | |
| Interact Power color Dark Gray #26008 | Yes | Yes | Yes |
| or Customer Specified Color | Yes | Yes | Yes |
| Redundant Input available | No | No | No |

Power Distribution Units Engineered to Reduce Risk and Improve Performance.

Interact Power, Inc. * 1325 N Red Gum Ave, Suite 7 * Anaheim, CA 92806 * T: 714.632.5005 * F: 714.632.5006



51133 Series



The 51133 series is a three phase 19” rack mount power distribution unit that is 1 “u” (1 ¾”) high and 9” deep. This series has nine IEC320 C13 receptacles on the rear. This series comes standard with a branch rated circuit breaker. Standard options like remote control, filtering, and other options are available. The 51133 series comes in various current ratings depending on model, see the specs below.

Model Selection Guide

| Model Number | 51133-00005-015 | 51133-00005-020 | 51133-00005-030 |
|---|------------------|------------------|------------------|
| Height x Width x Depth: | 1.75" x 19" x 9" | 1.75" x 19" x 9" | 1.75" x 19" x 9" |
| Voltage Input/Output (50-60Hz): | 230/400V~ | 230/400V~ | 230/400V~ |
| Current Input per phase: | 15Amps | 20Amps | 30Amps |
| Current Output De-rated per phase: | 12Amps | 16Amps | 24Amps |
| Full Load Volt/Amp De-rated per phase: | 2760VA | 3680VA | 5520VA |
| Combined Full Load Volt/Amp De-rated all phase: | 8280VA | 11040VA | 16560VA |
| NEMA Outlets: | 9, C13 | 9, C13 | 9, C13 |
| Circuit Breaker w/Kick Guard: | 3, 15Amp | 3, 20Amp | 3, 15/15 |
| Power Cord/Length (rear panel): | 16A "HAR"/15ft | 32A "HAR"/15ft | 32A "HAR"/15ft |
| NEMA Power Input Plug: | n/a | n/a | n/a |
| Front Panel Color | Clear Zinc | Clear Zinc | Clear Zinc |

Standard Options Available:

| | | | |
|--|-----|-----|-----|
| Customer Private Label: | Yes | Yes | Yes |
| EMI Filter w/ transient protection: | Yes | Yes | Yes |
| Remote Control : | Yes | Yes | Yes |
| Painted Front Panel: | | | |
| Interact Power color Dark Gray #26008 | Yes | Yes | Yes |
| or Customer Specified Color | Yes | Yes | Yes |
| Redundant Input available | No | No | No |

Power Distribution Units Engineered to Reduce Risk and Improve Performance.

Interact Power, Inc. * 1325 N Red Gum Ave, Suite 7 * Anaheim, CA 92806 * T: 714.632.5005 * F: 714.632.5006